ERNST P. AB Tel: +46-(0)31-703 07 70



Rubinol Putty Product Description

Rubinol Putty is a putty for reparations of scratches / damages in indoor wooden or laminate flooring, furniture or other interiors. It comes in 16 different nuances to match several wood species.

- It is easy to use
 - Solvent free
- Results in a hard and resistant repair which joins the wood in a natural way.
 The putty remains elastic enough to follow the material in its changes according to humidity and temperature. This results in a long lasting and beautiful reparation.

Technical data

Type of putty: Putty which contains linseed oil

Usage: Filling of cracks, knot holes etc

Pigment: Natural pigments **Density:** Ca 1,85 kg/dm³

Drying time: 15 min - 2 hours depending on size of

damage

Harmful: Classified as a not hazardous product to

health or environment.

Flammability: Not a flammable product

Storage time: Several years in an unopened original

packaging (aluminium tube)

Frost resistant: To be kept away from frost. If frozen,

product might still be able to use after

defrosting and some stirring.

Tools: Preferably use a plastic spatula to apply

the putty

Packaging: Aluminium tube containing 100 gram

Preparations

The surface to be repaired with Rubinol Putty should be well grinded, dry and free from waxes, fats and other impurities.

Remove excess putty immediately. Before it has dried the putty can be washed away with water.

To ensure a good optical result with the surrounding surface, treat the reparation with the same type of surface treatment (lacquer, oil, wax). This also prolongs the reparations life time.